



# i15 HIGH-EFFICIENCY LOUDSPEAKER





i15
HIGH-EFFICIENCY
LOUDSPEAKER



#### **Features**

- High fidelity output for professional applications.
- Ultra flattened full spectrum for demanding reproduction of sound for varies applications.
- HF compression driver with high efficiency & lightweight advantages.
- Well tuned LF vented enclosure provides an accurate response.
- · Symmetric enclosure for easy installation.
- High-quality Passive crossover design with high-grade components.

### **Applications**

- Portable systems indoor / outdoor
- PA system for small to medium size venue
- Bar / lounge installations
- Conferencing & broadcasting
- Club installation
- Corporate AV

- · Filling for High output system
- House of worship

## **Specification**

System Configuration: 2way full range monitor

Components: LF 1 x 15-inch excellent linearity high efficiency transducer

HF 1 x driver 1-1/3-inch Pure Titanium Diaphragm 1" exit on 90 H X 60 V horn

Frequency Response: +/-3dB 75 Hz to 18k Hz -10dB 55 Hz to 20k Hz

Sensitivity SPL (@ 1W - @1m): 100.5 dB

**Crossover Point: 1.8kHz** 

Impedance: 8  $\Omega$ 

Power Rating: Continuous 350W Program 500W Peak 1000W

Calculated Maximum Sensitivity: Continuous 126.9dB Program 128.4dB Peak 131.5dB

Coverage Angle: Horizontal 90° - Vertical 60°

#### **Construction info**

Enclosure: Trapezoidal construction Multi-layer birch plywood constructed

Finishing: Cabinet: water-based black / white / red (custom colors available) texture paint

**Grill: Black Powdered Paint** 

Mounting Hardware: 12 x M8 eyebolt point 3 x handle (wooden) 1 x pole piece (aluminium)

Connectors: 2 x neutrik speakon NL4


Protective Grille: 15 gauge hexagon perforated steel Dimensions: 712mm(H) x 461mm(W) x 613.5mm(D)

Packing Dimensions: 765mm (H) x 510mm(W) x 665mm(D) Volume: 0.2014cbm


Net Weight: 24kgs (52.8lbs) Gross Weight: 26.5kgs (58.3lbs)



## **Frequency Response Curve**



# **Impedance Magnitude Curve**





**Solutions By Syncrotek:** 











■5407 Bandera Rd, Ste. 111, San Antonio, TX 78238, USA

Phone: +1 (210) 251 4767

info@syncrotek.com

www.syncrotek.com